

PP Drainage & Sewer Systems

GWR0230090

BlackMax® PVC Bend DN300 x 90° FF RRJ



Application

Stormwater drainage

Features

- Australian made
- Light weight
- Ease of assembly
- Efficient design
- Low cost

Technical Data


Product Properties

Material	PVC
Colour	Black external wall with white internal bore
Approximate mass	13.5
Additional Information	Requires 2 x DN300 BlackMax Rubber Ring Iplex Code: GERSEW300

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Nominal Size	300MM
Angle (degrees)	90°
Dimension 'I'	311 mm



Jointing Details

Joint type	FF RRJ
Rubber ring material	Styrene Butadiene Rubber (SBR)
Average number of joints per Litre - lubricant	28
Maximum socket deflection	up to 2°

PP Drainage & Sewer Systems

GWR0230090
BlackMax® PVC Bend DN300 x 90° FF RRJ

Standards

Environmental Declarations and Standards

Product standard	AS/NZS1260 PVC-U pipes and fittings for drain, waste and vent applications' & 'AS/NZS 5065 'Polyethylene and polypropylene pipes and fittings for drainage and sewerage applications'
------------------	---

Material Properties

Mechanical

Density 'Specific Gravity'	1.45
----------------------------	------

Thermal

Coefficient of thermal expansion	$7 \times 10^{-5} / ^\circ \text{C}$
Allowable Operating Temperature - Degrees	Up to 50°C. Re rating is applied for Temperatures >30°C

Need help? | Merchants 1300 0 47539 | Civil 13 10 86

www.iplex.com.au