PVC Non Pressure

610150

150 HD COND COUP ORG ELEC




Technical Data

Product Properties

Material	PVC
Colour	Orange
Approximate mass	1.8 kg

Product Dimensions

Nominal size	150 mm



DN	L1	L2	L3	D1	D2	WALL THICKNESS
150	150	75	375	160.8	179.4	9.3

Packaging Information

Carton quantity	6

Jointing Details

Joint type	SWJ

PVC Non Pressure

610150

Material Properties

Mechanical

Density 'specific gravity'	1.43 - 1.5
Poissons ratio	0.38

Thermal

Coefficient of thermal expansion	7x10-5 /°C
Thermal conductivity	0.138 - 0.150 W.m-1°C-1

Fire Resistance

Flammability	Will not support combustion
Ignitability - AS 1530*	7
Smoke development - AS 1530*	9
Spread of flame - AS 1530*	0
Heat evolved - AS 1530*	2

*AWTA test report number 7-558788-CV

Electrical

Volume resistivity	1015 ohm.cm
Surface resistivity	≥ 10^13 Ω

© Iplex Pipelines Australia Pty Limited 2026. Images are for illustration purposes only. All drawings and information contained within this document are the exclusive property of Iplex. Iplex reserves the right to change product specifications and other information without prior notification. Measurements provided are for reference purposes only. Information in this publication is given in good faith and no warranty is provided or is to be implied with respect to either the information or the product, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Iplex_PVC CONDUIT_610150_datasheet_03Nov26