


PP Drainage & Sewer Systems

GWR2430090

BlackMax® PVC Equal Tee DN300 FFF Max RRJ Grey/White



Application

Stormwater drainage

Features

- Allows 90° branch connection
- Polypropylene
- Compatible with BlackMax® pipe
- RRJ
- Lightweight
- Corrosion resistant
- Provides complete plastic system with BlackMax® pipes

Technical Data


Product Properties

Material	PVC
Colour	Black external wall with white internal bore
Approximate mass	16.0 kg
Additional Information	Requires 3 x DN300 BlackMax® Rubber Ring Iplex Code: GERSEW300

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Nominal Size	300 mm
Angle (degrees)	90°
Dimension 'I'	564 mm



Jointing Details

Joint type	RRJ
Rubber ring material	Styrene Butadiene Rubber (SBR)
Average number of joints per Litre - lubricant	28
Maximum socket deflection	up to 2°

PP Drainage & Sewer Systems

GWR2430090
BlackMax® PVC Equal Tee DN300 FFF Max RRJ
Grey/White

Standards

Environmental Declarations and Standards

Product standard

AS/NZS1260 PVC-U pipes and fittings for drain, waste and vent applications' & 'AS/NZS 5065 'Polyethylene and polypropylene pipes and fittings for drainage and sewerage applications'

Material Properties

Mechanical

Density 'Specific Gravity'

1.45

Thermal

Allowable Operating Temperature - Degrees

Allowing Operating Temperature. Up to 50°C Re rating is applied for Temperatures >30°C

Need help? | Merchants 1300 0 47539 | Civil 13 10 86
www.iple.com.au