

PSSDRILL150

150 PRESS S1 PIPE SWJ X6M - DRILL CASING



Features

Technical Data

Product Properties

Material	PVC
Colour	White
Approximate mass	28.543 kg
Unprotected UV exposure	2 Years

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Minimum effective length	6000 mm
Nominal Size	150 mm
Min socket length	125 mm

Packaging Information

Crate quantity	33
----------------	----

Jointing Details

Joint type	SWJ
Minimum radius of pipe curvature	45 m
Maximum socket deflection	0

PSSDRILL150

Standards

Environmental Declarations and Standards

Environmental declaration	Iplex PVC Pressure Pipes EPD®
---------------------------	-------------------------------

Material Properties

Mechanical

Tensile yield strain (50 mm/min)	0.055
Tensile yield stress (50 mm/min)	3200MPa
Hardness shore D	85
Compressive Strength	66MPa

Thermal

Coefficient of thermal expansion	$7 \times 10^{-5}/^{\circ}\text{C}$
Specific heat	1047 J/kg/ $^{\circ}\text{C}$

Fire resistance

Flammability	Will not support combustion
Spread of flame - AS 1530*	0

*AWTA test report number 7 - 558788-CV

Need help? | Merchants 1300 0 47539 | Civil 13 10 86

www.iple.com.au