

PVC Non Pressure

E007150SLIP

150 PVC HD COND COUP FF ORG ELEC-SLIP - PVC TO PVC SW



Technical Data

Product Properties

Material	PVC
Colour	Orange
Approximate mass	2.0 kg
Unprotected UV exposure	3 months

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Nominal Size	150 mm
--------------	--------

Packaging Information

Carton Quantity	6
-----------------	---

Joining Details

Joint type	SWJ
------------	-----

Standards

Environmental Declarations and Standards

Product standard	Referenced Australian electrical and telecommunications product standards include: AS/NZS 2053 (various parts),AS/NZS 4296,AS/NZS 5033,AS 4702
------------------	--

PVC Non Pressure

E007150SLIP

Material Properties

Mechanical

Density 'Specific Gravity'	1.43 - 1.5
Poissons ratio	0.38

Thermal

Coefficient of thermal expansion	7x10 ⁻⁵ /°C
Thermal conductivity	0.138 W/m.K

Fire resistance

Flammability	Will not support combustion
Ignitability - AS 1530*	7
Smoke Development - AS 1530*	9
Spread of flame - AS 1530*	0
Heat evolved - AS 1530*	2

*AWTA test report number 7 - 558788-CV

Electrical

Volume resistivity	10 ¹⁵ ohm.cm
Surface resistivity	≥ 10 ¹³ Ω

Need help? | Merchants 1300 0 47539 | Civil 13 10 86

www.iplex.com.au