

PE Systems

PEAMI025020SS

Poly Adaptor DN25 x 0.750IN SDR11 Spig - MI ST/ST

Application

Joins to PE pipes or long spigot fittings to allow a BSP thread connection

Features

- Lightweight
- Durable
- Long service life
- Environmentally friendly
- Corrosion and chemical resistance

Technical Data

Product Properties

Material	Polyethylene
Colour	Black
Approximate mass	0.12 kg
Unprotected UV exposure	99.9% UV stable (black only)
End Connection	Spigot for electrofusion only -Male BSP
Rating	SDR11

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Nominal Size	25 mm
--------------	-------

Jointing Details

Joint type	Electrofusion
------------	---------------

Standards

Environmental Declarations and Standards

Product standard	AS/NZS 4129 'Fittings for polyethylene (PE) pipes for pressure applications'
------------------	--

PE Systems

PEAMI025020SS

Material Properties

Thermal

Thermal conductivity	0.38w/M.k
----------------------	-----------

Fire resistance

Flammability	Flammable
--------------	-----------

*AWTA test report number 7 - 558788-CV

Need help? | Merchants 1300 0 47539 | Civil 13 10 86

www.iplux.com.au