

PP Drainage & Sewer Systems

GR0275022

BlackMax® PP Bend DN750 x 22.5° FF RRJ



Application

Stormwater drainage

Features

- Australian made
- Light weight
- Ease of assembly
- Efficient design
- Low cost

Technical Data

Product Properties

Material	POLYPROPYLENE
Colour	Black external wall with yellow internal bore
Approximate mass	48.5 kg
Additional Information	Requires 2 x DN750 BlackMax Rubber Rings Iplex Code: GERSEW750

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Nominal Size	750
Angle (degrees)	22.5°
Dimension 'I'	TBC

Joining Details

Joint type	FF RRJ
Rubber ring material	Styrene Butadiene Rubber (SBR)
Maximum socket deflection	up to 2°

Standards

Environmental Declarations and Standards

Product standard	AS/NZS 5065 'Polyethylene and polypropylene pipes and fittings for drainage and sewerage applications'
------------------	--

PP Drainage & Sewer Systems

GR0275022
BlackMax® PP Bend DN750 x 22.5° FF RRJ

Material Properties

Mechanical

Density 'Specific Gravity'	0.9
----------------------------	-----

Thermal

Coefficient of thermal expansion	15 x 10-5 / ° C
Allowable Operating Temperature - Degrees	Up to 50 °C. Re rating is applied for Temperatures >20°C

Need help? | Merchants 1300 0 47539 | Civil 13 10 86

www.iplex.com.au