



GM301C99G						
Item No.	Document No.	Rev	Title	Material	Qty	Mass
1	2817	C	914x914 C/O Concrete Infill Cover Class G	Ductile Iron 500-10	1	206.3 kg
2	2821	C	914 mm UC Bar Class G	Ductile Iron 500-10	1	17.9 kg
3	2825	C	914 mm DC Bar Class G	Ductile Iron 500-10	1	18.1 kg
4	2829	C	914 mm LH Side Bar Class G	Ductile Iron 500-10	1	16.8 kg
5	2833	C	914 mm RH Side Bar Class G	Ductile Iron 500-10	1	16.8 kg
6	2917	A	M12 Washer	Nylon, general purpose	4	0.0 kg
7	2918	A	M12 Washer	Stainless Steel, A4-70	4	0.0 kg
8	5995	A	M12x85 Socket Head Cap Bolt	Stainless Steel, A4-70	4	0.4 kg
9	2854	C	Plastic Plug Ø26 mm	UV Stabilized Nylon	4	0.0 kg
10	1681	A	Plastic Keyhole Plug	UV Stabilized Nylon	4	0.0 kg

REVISION	D	28-05-20	MODIFIED TO COMPLY WITH AS 3996 : 2019	F.M.	S.S.	UNLESS OTHERWISE STATED ALL MEASURES IN MILLIMETERS. GENERAL CAST TOLERANCES: CT9 to ISO 8062. CASTING RADII: 3 mm DRAFT TAPERS: 2°	LINEAR MACHINING TOLERANCE: X. ±0.25 mm X.X ±0.10 mm  ANGULAR MACHINING TOLERANCE: X. ±0.5° X.X ±0.1°	NOM = Nominal; O/A = Overall; TYP = Typical; C/O = Clear Opening  <b>FINISH:</b> ALL CAST SURFACES TO BE PAINTED AS SPECIFIED. FABRICATED COMPONENTS TO BE HOT DIP GALVANISED TO AS4680. LIGHT FILM OF GATIC SEALING GREASE TO BE APPLIED ON ALL MACHINED SURFACES.			DESIGNED:	S.S.	16-09-08	CODE: GM301C99G	TITLE: 914x914 C/O CONCRETE INFILL COVER & FRAME ASSY CLASS G
	C	13-05-13	FRAMES MODIFIED	F.M.	S.S.						SCALE: N.T.S.	MASS: 276.3 kg			
	B	21-08-09	MARKINGS LAYOUT UPDATED ON COVER	F.M.	S.S.						CHECKED:	S.S.	14-01-09	FORMAT: A3	DRG. No: 2842
	A	14-01-09	INITIAL RELEASE.	F.M.	S.S.						APPROVED:	H.B.	14-01-09	SHEET: 1 of 1	REV: D
	No	DATE	DESCRIPTION	BY	CKD.										

Copyright : Gatic Pty Ltd - 2013