PP Drainage & Sewer Systems

GERSEW525

BlackMax®/SewerMax® SBR Rubber Ring Seal DN525 Black

Application

DN525 BlackMax®/SewerMax® pipe and fittings rubber ring seal

Features

- Easy to assemble
- Resistant to dislodging during jointing process
- Long service life
- Chemical resistance
- Allows Watertight joint
- Resistant to root intrusion
- Weatherability

Technical Data

Product Properties

Material	RUBBER
Colour	Black
Approximate mass	1.4 kg
Additional Information	For use with BlackMax® or SewerMax® pipes or fittings

*For short term, intermittent exposure. Contact Iplex for further details

Product Dimensions

Nominal Size	525 mm

Jointing Details

Rubber ring material	Styrene Butadiene Rubber (SBR)

Standards

Environmental Declarations and Standards

Product standard	AS1646 'Elastomeric seals for waterworks purposes'

Material Properties

Mechanical

Density 'Specific Gravity'	1.45

© Iplex Pipelines Australia Pty Limited 2026. Images are for illustration purposes only. All drawings and information contained within this document are the exclusive property of Iplex. Iplex reserves the right to change product specifications and other information without prior notification. Measurements provided are for reference purposes only. Information in this publication is given in good faith and no warranty is provided or is to be implied with respect to either the information or the product, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application.Iplex_BLACK MAX_GERSEW525_datasheet_11Aug26