



GM301C97B						
Item #	Drwg #	Rev #	Title	Material	Qty	Mass [kg]
1	2770	B	914x762 C/O Concrete Infill Cover Class B	Ductile Iron 500-10	1	81.2 kg
2	2707	C	914 mm Under Cut Bar Class B	Ductile Iron 500-10	1	6.3 kg
3	2706	C	914 mm Draw Cut Bar Class B	Ductile Iron 500-10	1	6.7 kg
4	2726	B	762 mm LH Side Bar Class B	Ductile Iron 500-10	1	5.3 kg
5	2727	B	762 mm RH Side Bar Class B	Ductile Iron 500-10	1	5.3 kg
6	6011	A	M12x40 Socket Head Cap Bolt	Stainless Steel, A4-70	2	0.1 kg
7	6012	A	M12 Washer	Stainless Steel, A4-70	2	0.0 kg
8	2917	A	M12 Washer	Nylon, general purpose	2	0.0 kg
9	2854	C	Plastic Plug Ø26 mm	UV Stabilized Nylon	2	0.0 kg
10	1681	A	Plastic Keyhole Plug	UV Stabilized Nylon	2	0.0 kg

REVISION B 20-11-20 COMPONENTS REVISED TO COMPLY TO AS 3996:2019 F.M. S.S. A 25-06-08 INITIAL RELEASE F.M. M.K. No DATE DESCRIPTION BY CKD.		UNLESS OTHERWISE STATED ALL MEASURES IN MILLIMETERS. GENERAL CAST TOLERANCES: CT9 to ISO 8062. CASTING RADII: 3 mm DRAFT TAPERS: 2°		LINEAR MACHINING TOLERANCE: X. ±0.25 mm X.X ±0.10 mm ANGULAR MACHINING TOLERANCE: X. ±0.5° X.X ±0.1°		NOM = Nominal; O/A = Overall; TYP = Typical; C/O = Clear Opening FINISH: ALL CAST SURFACES TO BE PAINTED AS SPECIFIED. FABRICATED COMPONENTS TO BE HOT DIP GALVANISED TO AS/NZS 4680. LIGHT FILM OF GATIC SEALING GREASE TO BE APPLIED ON ALL MACHINED SURFACES.		GATIC GATIC PTY LTD 9-15 Radford Road, PO Box 312, Reservoir VIC. 3073 Ph: 03 9316 2666 Fax: 03 9315 0099 www.gatic.com.au		THIRD ANGLE PROJECTION		CODE: GM301C97B SCALE: N.T.S. FORMAT: A3 SHEET: 1 of 1		TITLE: 914x762 C/O CONCRETE INFILL COVER & FRAME ASSEMBLY CLASS B MATERIAL: MASS: 104.9 kg DRG. No: 2792 REV: B	
---	--	---	--	---	--	--	--	--	--	------------------------	--	---	--	--	--

© Copyright : Gatic Pty Ltd - 2020