




FILLER MATERIAL TO BE ADDED



SECTION B-B



SECTION A-A

GM301S96B						
Item #	Drwg #	Rev #	Title	Material	Qty	Mass (kg)
1	2893	C	914x610 C/O rec solidtop Cvr Class B	Ductile Iron 500-10	1	64.2 kg
2	2707	C	914 mm Under Cut Bar Class B	Ductile Iron 500-10	1	6.4 kg
3	2706	C	914 mm Draw Cut Bar Class B	Ductile Iron 500-10	1	6.7 kg
4	2703	B	610 mm RH Side Bar Class B	Ductile Iron 500-10	1	4.3 kg
5	2704	B	610 mm LH Side Bar Class B	Ductile Iron 500-10	1	4.3 kg
6	6011	A	M12x40 Socket Head Cap Bolt	Stainless Steel, A4-70	2	0.1 kg
7	6012	A	M12 Washer	Stainless Steel, A4-70	2	0.0 kg
8	2917	A	M12 Washer	Nylon, general purpose	2	0.0 kg
9	2854	C	Plastic Plug Ø26 mm	UV Stabilized Nylon	2	0.0 kg
10	1681	A	Plastic Keyhole Plug	UV Stabilized Nylon	2	0.0 kg

REVISION	No	DATE	DESCRIPTION	BY	CKD.
B	26-08-20		COVER AND FRAME REVISED.	F.M.	S.S.
A	08-01-09		INITIAL RELEASE.	F.M.	S.S.

UNLESS OTHERWISE STATED
 ALL MEASURES IN MILLIMETERS.
 GENERAL CAST TOLERANCES: CT9 to ISO 8062.
 CASTING RADII: 3 mm
 DRAFT TAPERS: 2°


LINEAR MACHINING TOLERANCE:
 X. ±0.25 mm
 X.X ±0.10 mm

ANGULAR MACHINING TOLERANCE:
 X. ±0.5°
 X.X ±0.1°

NOM = Nominal; O/A = Overall; TYP = Typical; C/O = Clear Opening

FINISH: ALL CAST SURFACES TO BE PAINTED AS SPECIFIED. FABRICATED COMPONENTS TO BE HOT DIP GALVANISED TO AS4680. LIGHT FILM OF GATIC SEALING GREASE TO BE APPLIED ON ALL MACHINED SURFACES.

GATIC PTY LTD
 9-15 Radford Road, PO Box 312, Reservoir VIC. 3073
 Ph- 03 9316 2666 Fax- 03 9315 0099 www.gatic.com.au



DESIGNED:	F.M.	29-06-08
DRAWN:	F.M.	08-01-09
CHECKED:	S.S.	08-01-09
APPROVED:	H.B.	08-01-09

CODE: GM301S96B
 SCALE: N.T.S.
 FORMAT: A3
 SHEET: 1 of 1

TITLE: 914x610 C/O SOLID TOP COVER & FRAME ASSY CLASS B
 MATERIAL: MASS: 86.0 kg
 DRG. No: **3146**
 REV: B