



GM301C1245D						
Item #	Drwg #	Rev #	Title	Material	Qty	Mass (kg)
1	6080	A	1218x457 C/O Concrete Infill Cover Class D	Ductile Iron 500-10	1	110.3 kg
2	4021	C	1298 mm DC Bar	Ductile Iron 500-10	1	19.4 kg
3	4022	C	1298 mm UC Bar	Ductile Iron 500-10	1	16.1 kg
4	4001	D	527 mm LH Side Bar	Ductile Iron 500-10	1	7.7 kg
5	4002	D	527 mm RH Side Bar	Ductile Iron 500-10	1	7.7 kg
6	2917	A	M12 Washer	Nylon, general purpose	2	0.0 kg
7	2918	A	M12 Washer	Stainless Steel, A4-70	2	0.0 kg
8	5992	A	M12x70 Socket Head Cap Bolt	Stainless Steel, A4-70	2	0.2 kg
9	2854	C	Plastic Plug Ø26 mm	UV Stabilized Nylon	2	0.0 kg
10	1681	A	Plastic Keyhole Plug	UV Stabilized Nylon	6	0.0 kg

REVISION	No	DATE	DESCRIPTION	BY	CKD.	UNLESS OTHERWISE STATED ALL MEASURES IN MILLIMETERS. GENERAL CAST TOLERANCES: CT9 to ISO 8062. CASTING RADII: 3 mm DRAFT TAPERS: 2°	LINEAR MACHINING TOLERANCE: X. ±0.25 mm X.X ±0.10 mm ANGULAR MACHINING TOLERANCE: X. ±0.5° X.X ±0.1°	NOM = Nominal; O/A = Overall; TYP = Typical; C/O = Clear Opening FINISH: ALL CAST SURFACES TO BE PAINTED AS SPECIFIED. FABRICATED COMPONENTS TO BE HOT DIP GALVANISED TO AS/NZS 4680. LIGHT FILM OF GATIC SEALING GREASE TO BE APPLIED ON ALL MACHINED SURFACES.			DESIGNED:	F.M.	27-11-20	CODE:	GM301C1245D	TITLE:	1218x457 C/O CONCRETE INFILL COVER & FRAME ASSEMBLY CLASS D	MASS:	161.5 kg
	A	27-11-20	INITIAL RELEASE.	F.M.	S.S.						CHECKED:	F.M.	27-11-20	SCALE:	N.T.S.	FORMAT:	A3	DRG. No:	6083