





NOTE:  
 FRAME COMPONENTS  
 ASSEMBLED USING 8 OFF M10x40  
 HEX BOLTS C/W WASHERS AND  
 NUTS



SECTION B-B



SECTION A-A

GM301S77D						
Item No.	Drwg.	Rev.	Title	Material	Qty.	Mass (kg)
1	2193	D	762x762 C/O Solid Top Cover Class D	Ductile Iron 500-10	1	93.4 kg
2	1681	A	Plastic Keyhole Plug	UV Stabilized Nylon	4	0.0 kg
3	4009	D	762mm LH Side Bar Class D	Ductile Iron 500-10	1	12.0 kg
4	4011	D	762mm RH Side Bar Class D	Ductile Iron 500-10	1	12.0 kg
5	4012	C	762mm Under Cut Bar Class D	Ductile Iron 500-10	1	11.2 kg
6	4008	C	762mm Draw Cut Bar Class D	Ductile Iron 500-10	1	13.5 kg
7	2917	A	M12 Washer	Nylon, general purpose	2	0.0 kg
8	2918	A	M12 Washer	Stainless Steel, 304	2	0.0 kg
9	5992	A	M12x70 Socket Head Cap Bolt	Stainless Steel, 304	2	0.1 kg
10	2854	C	Plastic Plug Ø26 mm	UV Stabilized Nylon	2	0.0 kg

Copyright : Gatic Pty Ltd - 2020

REVISION	No	DATE	DESCRIPTION	BY	CKD.
B	10-12-20		MODIFIED TO COMPLY WITH AS 3996 : 2019	F.M.	S.S.
A	04-02-15		INITIAL RELEASE	F.M.	S.S.

**UNLESS OTHERWISE STATED**  
 ALL MEASURES IN MILLIMETERS.  
 GENERAL CAST TOLERANCES:  
 CT9 to ISO 8062.  
 CASTING RADII: 3 mm  
 DRAFT TAPERS: 2°

LINEAR MACHINING TOLERANCE:  
 X. ±0.25 mm  
 X.X ±0.10 mm

ANGULAR MACHINING TOLERANCE:  
 X. ±0.5°  
 X.X ±0.1°

NOM = Nominal; O/A = Overall; TYP = Typical; C/O = Clear Opening

**FINISH:** ALL CAST SURFACES TO BE PAINTED AS SPECIFIED. FABRICATED COMPONENTS TO BE HOT DIP GALVANISED TO AS4680. LIGHT FILM OF GATIC SEALING GREASE TO BE APPLIED ON ALL MACHINED SURFACES.

**GATIC**  
 GATIC PTY LTD  
 9-15 Radford Road, PO Box 312, Reservoir VIC. 3073  
 Ph- 03 9316 2666 Fax- 03 9315 0099 www.gatic.com.au

THIRD ANGLE PROJECTION

DESIGNED:	BY	DATE
	--	--
DRAWN:	BY	DATE
	F.M.	04-02-15
CHECKED:	BY	DATE
	S.S.	04-02-15
APPROVED:	BY	DATE
	H.B.	04-02-15

CODE: GM301S77D  
 SCALE: N.T.S.  
 FORMAT: A3  
 SHEET: 1 of 1

TITLE: 762x762 C/O SOLID TOP COVER & FRAME CLASS D - ASSEMBLY  
 MATERIAL: --  
 MASS: 142.3 kg  
 DRG. No: **5072**  
 REV: B